Frontiers of Multidisciplinary Exploration
Volume 2, Issue 1, March 2026, Page 1-13
ISSN: 3139-4086

Artificial Intelligence for Tool Chatter Detection and Monitoring: A Review

Yogesh Shrivastava[1], Bhagat Singh[2]

[1]Galgotias College of Engineering and Technology, Greater Noida, U.P., India
[2]Jaypee University of Engineering and Technology, Guna, M.P., India

*Corresponding author's Email: bhagatmech@gmail.com

Received 25 Nov 2025, Accepted 26 Feb 2026, Published online: 30 March 2026

Abstract

Chatter of tools is the major drawback of machining processes which causes poor surface finish, reduced tool life and low productivity. Traditional methods of chatter detection, which are mainly founded on signal processing and analytical models, are not usually flexible with different cutting conditions. Artificial intelligence (AI) has emerged as the way of providing efficient solution to strong and real-time chatter observation in the recent past. In this review, the AI-based tool chatter detection methods are briefly discussed in a short discussion including machine learning methods such as support vector machines, decision trees, and k-nearest neighbors, and deep-learning-based methods such as convolutional and recurrent neural networks. Vibration, acoustic emission and force signal are also other sensor input presented in feature extraction and model development. In the paper, the latest evolution about the intelligent monitoring systems and the key issues of the system such as data dependency, generalization and complications of computation are also observed. The future trends are on explainable AI and adaptive learning to maintain stable machining performance.

Keywords: Tool Chatter Detection; Artificial Intelligence; Machine Learning; Deep Learning; Smart Manufacturing

1. Introduction

The vibration effect is a self-excitatory effect known as tool chatter, which occurs when machining processes such as turning, milling and drilling [1-4]. It has negative impacts on the quality of surfaces, dimensional precision, tool life and productivity. The real time chatter detection and control has become more meaningful in the contemporary manufacturing where accuracy and efficiency are the most important factors.

Traditional methods of chatter detection are mainly analytical modeling and signal processing methods such as stability lobe diagrams, Fourier analysis, time-frequency techniques [5-7]. Although these methods provide simple insights into machining dynamics, they may be influenced by the critical system modeling and less efficient in the case of various cutting conditions, tool wear and material variation.

Frontiers of Multidisciplinary Exploration
Volume 2, Issue 1, March 2026, Page 1-13
ISSN: 3139-4086

The new trends in the area of artificial intelligence (AI) have provided fresh opportunities of smart and responsive chatter detection frameworks [8-10]. AI-based methods have the ability to acquire complicated patterns on sensor data and allow real-time monitoring without explicit physical models. The aim of the review is to comment on the relevance of AI-based tool chatter detection and monitoring, the recent achievements, the issues of interest, and the future research directions.

In order to give a comprehensive view of AI-based chatter monitoring systems, a generalized scheme of how sensing, signal processing, and intelligent decision-making are integrated is given in Figure 1.




Figure 1: Framework of AI-Based Tool Chatter Detection and Monitoring System

As it is seen in Figure 1, sensor data acquired during the machining is processed and analyzed with the help of AI models which detect chatter and can be applied to implement real-time control actions. The modern intelligent manufacturing systems are built on this integrated system.

2. Literature Review

2.1 Classical Chatter Detection Techniques

Machining dynamics, analytical modeling, and signal processing approaches are the main basis of classical chatter detection techniques [11-13]. Such methods are used to detect the beginning of chatter based on the interaction of the cutting tool and the workpiece, which in many cases is represented as a dynamic system with regeneration effects. The stability lobe diagram (SLD) is one of the most popular tools of analysis that predicts the stable and unstable cutting regions in accordance with the spindle speed and depth of cut. SLDs are based on frequency response function (FRF) of a machine and can give good advice on the best machining parameters to use to prevent chatter [14-17]. Nevertheless, they rely heavily on the correct identification of the

systems and can be deteriorated in the changing conditions like tool wear, temperature change and material inhomogeneity.

Besides analytical models, time domain signal analysis has been applied widely in chatter detection. Root mean square (RMS), variance, kurtosis and skew of vibration or force signal are the common statistical indicators used to draw a line between stable and unstable cutting conditions [18-20]. Although these features are easily calculated, they can be insensitive to the slightest changes in machining dynamics and can cause a delay in their identification.

Frequency-domain analysis, especially Fast Fourier Transform (FFT) has also been extensively used to determine the prominent frequency contents related to chatter. The vibrations of the chatter are usually represented by separate peaks at the natural frequencies of the system. The FT-based tools are suitable in the steady state but not suitable in the non-stationary signals where chatter varies with time.

To overcome this, timefrequency analysis methods like Short-Time Fourier Transform (STFT), wavelet transform and HilbertHuang Transform (HHT) have been presented [21-24]. These methods provide time-dependent as well as spectral data, which assist in detecting chatter transient effects at a better level. They have found wavelet transform to be of much popularity due to the ability to analyze a signal at multiple non-uniform resolutions, which enables wavelet transform to be useful in feature localization.

The other strategy that is significant is that of acoustic emission (AE) signal, in which high-frequency stress waves produced during the cutting process are observed [25-27]. The AE signals are highly sensitive to even micro level changes in the cutting process and can hence be detected at a very early stage chatter. Nevertheless, they are vulnerable to noise as well and need to be carefully conditioned in terms of signals.

Although they are commonly used, the classical chatter detection methods have a number of limitations. They are very noise sensitive and environmental sensitive, they must have prior knowledge of the system dynamics and they are unable to accommodate change in machining conditions. Also, these methods tend to adopt hand-based feature detection and threshold classification, which is limiting to their power and scalability in complex manufacturing environments.

These problems have contributed to the movement towards data-driven and AI-based algorithms, which can fill the gaps of the old generation approaches due to their capacity to recognize chatter in adaptive, automated, and real-time.

2.2 Machine Learning-Based Approaches

As the classical approaches have their shortcomings, machine learning (ML) algorithms have attracted considerable interest as a solution to the problem of chatter detection because they are capable of learning patterns directly through data [28]. They do not use analytical models as heavily as the traditional methods, with the chatter detection problem in the ML methods being classified as a classification or regression problem, with machining states (stable or unstable) being determined based on the extracted features of sensor signals.

Early ML-based research made use of feature engineering methods to generate meaningful descriptors of time-domain, frequency-domain, and time–frequency cues. The most widely employed are statistical parameters (RMS, kurtosis, skewness), spectral peaks, energy distributions and wavelet coefficients of vibration, acoustic emission, and cutting force signals. These characteristics are then fed into different ML algorithms.

One of the most widespread algorithms is the support vector machines (SVM) whose performance has been remarkable in the sense that it can handle nonlinear classification and high generalization rate especially when the scale of data is small. Chatter prediction has also been done using artificial neural networks (ANN) which provides flexibility in the modeling of complex relationships between input features and machining conditions. On the same note, decision trees and random forests have explainable models and resistance to overfitting, whereas the k-nearest neighbors (KNN) is a simple but powerful method of recognizing patterns.

As compared to classical methods, the accuracy and flexibility of detection by ML-based solutions have been demonstrated to be higher. Their functioning is however extremely reliant on the quality of feature extraction and selection, and the methodologies are likely to need the domain understanding and may not be applicable to other machining systems. Besides, the model is often an issue in large-scale data and real-time implementation in instances where the feature computation is complex.

In spite of these difficulties, machine learning has provided the basis of intelligent chatter detection systems and is a continuum between conventional signal processing and new high-end deep learning methods.

2.3 Deep Learning Techniques

Deep learning (DL) is an emerging game changer concept in chatter detection that eliminates the need of hand crafted feature engineering, and allows one to learn directly on raw sensor data without the need of feature engineering [29]. Deep learning models have the capability to extract hierarchical features, which represent the complex trends in machining signals, by the use of multi-layer neural network architectures.

Convolutional neural network (CNN) is among the most widely used architectures, which are very useful in the processing of structured data such as time-series signals and spectrograms of the representations. CNNs are able to learn spatial features by converting vibration signal-to-timefrequency image (e.g. spectrograms or wavelet scalograms) signals, and are strong detectors of chatter. They also have the capability of extracting features automatically thereby drastically limiting the usage of the domain knowledge.

Besides CNNs, there are recurrent neural networks (RNNs) and more recent ones, including long short-term memory (LSTM) and gated recurrent units (GRU), which are used to produce temporal correlations between machining signals. These are the most appropriate sequential data models, and they can predict when chatter occurs by means of time learning. The LSTM based models have been found to perform highly in real time monitoring activities owing to their long term dependence feature.

Frontiers of Multidisciplinary Exploration
Volume 2, Issue 1, March 2026, Page 1-13
ISSN: 3139-4086

Recent research is also looking into hybrid deep learning models, including CNNLSTM architectures, which involve the use of spatial feature extraction and temporal modeling to improve performance. Moreover, autoencoders and unsupervised learning methods have facilitated detection of anomalies in a scenario where a limited amount of labeled data is available.

Although there are benefits, deep learning methods have various challenges such as large labeled data sets are required, large computational costs are required, and model interpretability is a challenge. Deep model training may be resource-demanding and their application in real-time industrial settings may need optimization and hardware, e.g., GPUs or edge devices.

However, deep learning is a major breakthrough in chatter detection, as it is more accurate, robust, and scalable. It is likely to be instrumental in the creation of intelligent and autonomous machining systems due to its combination with modern manufacturing technologies.

A comparative analysis of conventional machine learning and deep learning approaches in chatter detection is given in Table 1 to illustrate the differences between the two approaches.

Table 1. Machine Learning vs Deep Learning for Chatter Detection

Aspect	Machine Learning	Deep Learning
Feature Extraction	Manual	Automatic
Data Requirement	Moderate	High
Accuracy	Moderate to High	High
Computational Cost	Low to Medium	High
Real-Time Capability	Easier	Challenging (needs optimization)
Interpretability	Higher	Lower

Based on Table 1, it can be seen that deep learning methods are more accurate and can automatize feature extraction as compared to traditional machine learning. Nevertheless, they demand more computing power and bigger datasets and could not be practically implemented without optimization.

2.4 Sensor Technologies and Data Acquisition

The quality and type of sensor data obtained in machining is one of the key factors that determine the effectiveness of chatter detection systems [30]. Different sensing modalities have been examined to measure the dynamic nature of the cutting process with each having its own benefits and drawbacks.

The most commonly used are vibration sensors (accelerometers) because they are very sensitive to the dynamic conditions of machining. They are normally attached to the tool holder, spindle, or workpiece to measure tool-workpiece interactions. The signals of vibration are rich in information of both the time-domain and frequency-domain analysis and are

frequently employed in both classical and AI-based methods. The high-frequency elastic waves produced when cutting are detected by acoustic emission (AE) sensors. These sensors are very sensitive to micro-level occurrences like crack formation, plastic deformation, and friction, and hence they can be applied in detecting early chatter. Nevertheless, environmental noise frequently corrupts AE signals and sophisticated filtering and signal conditioning is necessary. During machining, cutting force sensors (e.g., dynamometers) determine forces in more than one direction. The signals give first-hand information about the cutting mechanics and are applicable in modeling and monitoring the stability of the processes. Although they are accurate, force sensors are not very cheap and do not necessarily be feasible to use in industries.

Cost-effective alternatives to chatter detection have also been considered including microphones and sound sensors. Though not as precise as vibration or AE sensors, they can provide non-contact measurement and are simple to install, and can be appealing to some applications. Multi-sensor data fusion has become a matter of major concern in recent years. Through the integration of data across several sensors, the researchers strive to enhance detection accuracy and robustness particularly in the noisy and varying conditions. The methods of data fusion may be applied to the feature-level or decision-level, which increases the credibility of AI-based models. Chatter monitoring has been upgraded with the introduction of wireless sensors and IoT-enabled systems of data acquisition. These systems provide real-time data collection, remote monitoring and easy integration with smart manufacturing platforms. Nevertheless, the data synchronization, bandwidth, and sensor position optimization are the obstacles that should be considered crucial.

The various sensing modalities are important in the performance of chatter detection. Table 2 provides a comparative overview of the commonly used sensors, their strengths, and weaknesses.

Table 2. Summary of Sensors Used in Chatter Detection

Sensor Type	**Measured Signal**	**Advantages**	**Limitations**	**Applications**
Accelerometer	Vibration	High sensitivity, widely used	Sensitive to noise	Milling, turning
Acoustic Emission (AE)	High-frequency stress waves	Early detection capability	Noise interference	Micro-machining
Dynamometer	Cutting forces	Direct measurement	Expensive, complex setup	Research, precision machining
Microphone	Sound	Low cost, non-contact	Low accuracy	Basic monitoring
Multi-Sensor Fusion	Combined signals	Improved reliability	Data complexity	Smart manufacturing

As it could be noticed, the most common are vibration and acoustic emission sensors because they are sensitive to machining dynamics. Nevertheless, it is becoming more popular to use multi-sensor fusion methods to enhance reliability and robustness in complex industrial settings.

2.5 Hybrid and Intelligent Systems

The current studies have concentrated on hybrid systems to address the drawbacks of the two methods by using classical signal processing methods alongside artificial intelligence methods. The aim of these systems is to make the best out of both worlds, strong feature extractors and adaptive learners of signal processing and AI respectively.

One popular hybrid method is to perform preprocessing of raw signals with wavelet transform, empirical mode decomposition (EMD) or variational mode decomposition (VMD) to extract meaningful features [31-32]. The processed features are then inputted into machine learning or deep learning models to classify or predict. Such combinations have been established to be considerably superior in detecting accuracy and strength particularly in a noisy environment.

The alternative direction that must be followed is the one of integrating the optimization algorithms (e.g., genetic algorithms, particle swarm optimization) and the AI models to better the feature selection, parameter tuning, and model performance. These hybrid models are optimistic, hence they help in achieving better generalization and reduce the complexity.

Smart monitoring systems, a combination of AI and Internet of Things (IoT), cloud computing, and edge computing, have also been created as a result of new innovations. These systems are real time and measure sensor data on the location (edge devices) or off-site (cloud platforms) and make fast and dynamic decisions. The edge-based hybrid models will be particularly handy in the industrial contexts in order to reduce latency and ensure the real-time responsiveness.

Also, closed-loop control systems are being studied, where chatter detection is connected to process control systems. The AI models of this type of systems are also used to not only identify the chatter but also dynamically adapt the machining settings (e.g. spindle speed, feed rate) to eliminate it during the production process in real time to create autonomous and self-optimizing production processes.

Although hybrid systems have their benefits, they add more complexity to the system design, data integration, and computation requirements. The ability to have smooth coordination among various components is a major issue. However, the trend of hybrid and intelligent systems is a good step towards realization of reliable, scalable and real-time chatter monitoring in contemporary manufacturing settings.

2.6 IoT and Smart Manufacturing Integration

The development of Industry 4.0 has greatly contributed to the creation of intelligent chatter monitoring systems as it allows the smooth integration of sensors, data analytics, and communication technologies [34]. The integration of the Internet of Things (IoT) enables real-time data collection of various sensors installed in machining systems and enables the ongoing observation of the process dynamics.

Frontiers of Multidisciplinary Exploration
Volume 2, Issue 1, March 2026, Page 1-13
ISSN: 3139-4086

Under IoT-based systems, sensor information like vibration, acoustic emission and cutting force messages are sent to central or distributed platforms to process and analyze. Cloud computing is essential in the management of massive data storage and in the provision of advanced analytics through AI models. Cloud-based systems, however, can cause latency, which can restrict their usefulness in more time-sensitive applications like real-time chatter suppression.

In order to overcome this drawback, edge computing has become an important facilitator of real-time decision-making. The processing of data and AI inference is done in a machine with edge-based architectures, which minimizes the latency and bandwidth needs. This enables the quick identification of chatter and instant corrections of the same, which is vital in keeping the machining stable.

Moreover, the idea of digital twins has become popular in the contemporary manufacturing. A digital twin is a simulated image of the actual machining system which continuously develops according to sensor data in the real-time. By introducing AI models into digital twins, it will be possible to simulate conditions during machining, predict the existence of chatter, and optimize process parameters in advance.

Keeping track of chatter IoT systems can be used to facilitate predictive maintenance, in which AI models compare both historical and real-time data to determine patterns related to tool wear, machine degradation, or upcoming failures. This increases the reliability of the system and minimizes downtimes.

Despite all these, such problems as data security, interoperability, standardization and system scalability are imperative. These issues are solved, which is the key to the mass implementation of the IoT-enabled chatter monitoring in the industrial environment.

In order to give a better idea on the different methods described in the literature, Table 3 presents a comparative overview of classical, machine learning, deep learning, hybrid, and IoT-based chatter detection methods.

Table 3. Comparison of Chatter Detection Techniques

Category	Techniques	Key Features	Advantages	Limitations
Classical Methods	SLD, FFT, Wavelet Transform, HHT	Analytical & signal-based	Simple, well-established, interpretable	Requires system modeling, less adaptive
Machine Learning	SVM, ANN, KNN, Decision Trees	Feature-based learning	Improved accuracy, adaptable	Depends on feature engineering
Deep Learning	CNN, RNN, LSTM, GRU	Automatic feature extraction	High accuracy, handles complex data	Needs large data, high computation
Hybrid Methods	WT + ML, EMD + DL,	Combines signal processing + AI	Improved robustness	Increased complexity

	Optimization-based		and performance	
IoT-Based Systems	Edge AI, Cloud AI, Digital Twin	Real-time monitoring & control	Scalable, smart manufacturing integration	Security, latency, infrastructure issues

Table 3 illustrates that classical approaches are easy to implement and interpret, but they are not flexible and efficient (compared to machine learning and deep learning methods which are more accurate and robust). The hybrid and IoT-based systems are more efficient, too, because they offer real-time monitoring and intelligent decision-making, but introduce additional complexity.

Despite the fact that the chatter detection techniques have been enhanced significantly, there exist several challenges. These challenges and potential directions of future research are summarized in Table 4.

Table 4. Key Challenges and Future Directions

Challenges	**Description**	**Future Directions**
Data Scarcity	Limited labeled datasets	Transfer learning, synthetic data
Generalization	Model fails across setups	Domain adaptation
Computational Cost	High for deep models	Edge AI, lightweight models
Interpretability	Black-box models	Explainable AI (XAI)
Real-Time Deployment	Latency issues	Edge computing, optimization
Integration	Complex system design	Standardized IoT frameworks

The solutions of these problems will be key to the development of robust, scaled and live chatter-monitoring systems. It is suggested that further research should be done to improve the generalization of models, reduce the complexity of computations and make them more interpretable in order to achieve acceptance in industry.

3. Key Findings from Literature

Based on literature, the development of chatter detection has experienced remarkable evolution from traditional analytical methods to intelligent, AI-based monitoring systems. Conventional methods, such as the Stability Lobe Diagrams (SLDs), Fast Fourier Transform (FFT), Wavelet Transform, Hilbert–Huang Transform (HHT) and Acoustic Emission (AE) analysis, provide reliable and interpretable solutions to identify the occurrence of machining instability. However, these techniques are heavily reliant on the accurate modeling of the system, handcrafted feature extraction, and pre-defined thresholds, and are less effective in the presence of different machining conditions, tool wear and environmental noises. As such, they may not always be suitable in dynamic industrial environments.

Chatter detection has been significantly improved thanks to the introduction of machine learning; these algorithms can learn complex relationships directly from sensor input. Some algorithms, like Support Vector Machines (SVM), Artificial Neural Networks (ANN), Decision Trees, Random Forests, and K-Nearest Neighbors (KNN), have shown higher accuracy of detection and better adaptability than conventional approaches. More recently, deep learning models, such as Convolutional Neural Networks (CNNs), Recurrent Neural Networks (RNNs), Long Short-Term Memory (LSTM) networks and Gated Recurrent Units (GRUs) have also shown improvements, as they automatically learn the discriminative features from the raw sensor signals without requiring manual feature engineering. While these techniques offer greater accuracy and robustness, they have drawbacks in terms of the need for large datasets of labeled examples, computational power and interpretability of the model.

The literature also focuses on sensor technologies to achieve reliable chatter detection. The most common sensors used are accelerometers and acoustic emission sensors, which are highly sensitive to the dynamics that occur during the machining process, and force sensors, which are more expensive but provide more accurate measurements. In recent years, several studies have shown that multi-sensor data fusion can improve detection accuracy and robustness, thanks to the fusion of complementary information provided by multiple sensing modalities. Besides, the hybrid methods combining advanced signal processing techniques, such as Wavelet Transform, Empirical Mode Decomposition (EMD), and Variational Mode Decomposition (VMD), and machine learning/deep learning models have demonstrated better performance especially in complex and noisy machining settings.

Another key discovery is the increasing adoption of Industry 4.0 technologies in chatter detection. Real-time monitoring, predictive maintenance, and smart process optimization have been made possible thanks to the integration of Internet of Things (IoT), cloud computing, edge computing, and digital twin technologies. In particular, edge computing processes sensor data near the machining equipment and allows for fast decision-making and adaptive control, which reduces latency problems. Moreover, more and more closed-loop control systems are designed to automatically adjust the various machining parameters, including spindle speed and feed rate, as soon as the chatter is detected, thereby enhancing the stability of the machining process, production efficiency, surface quality, and tool life.

Despite these improvements, existing literature poses some drawbacks such as lack of labeled datasets, the difficulty of models to generalize to other machining scenarios, high computational demands of deep learning-based models, low interpretability of deep learning models, and real-time industrial implementation difficulties. Towards this end, future research would focus on transfer learning, domain adaptation, Explainable Artificial Intelligence (XAI), lightweight edge-AI models, standardising IoT frameworks, and scalable intelligent manufacturing systems, all of which would facilitate the broader industrial adoption of chatter detection technologies based on AI.

4. Conclusion and Future Scope

The biggest problem with machining processes remains to be chatter detection and monitoring since it has a direct effect on the quality of products, the life of the tools, and efficiency. The paper has critically examined the classic, machine learning and deep learning technique of detecting tool chatter, and the modern tendencies of sensor technologies, hybrid and smart

combination and manufacturing. Although classical methods are fundamental, they are constrained by the need to have an accurate system model and are not adaptable. Machine learning methods have enhanced the detection abilities of the data-driven methods but are based on manual features. Deep learning models have also contributed to the development of the field by allowing automatic feature extraction and high accuracy, but they are also costly in terms of computational resources and large data sets. The combination of AI and IoT, edge computing, and digital twins has created new opportunities of real-time and intelligent chatter monitoring systems. These developments are leading to self-organizing and self-optimizing manufacturing systems.

The future research ought to concentrate on making strong and generalizable models that can adjust to different machining environments. Explainable AI (XAI) needs to be applied to enhance transparency and trust in AI-based decisions. Also, there is transfer learning and few-shot learning that can be used to solve the problem of limited labelled data. Real-time performance will also be improved with the creation of lightweight models of edge deployment and the implementation of closed-loop control systems.

References:

[1] Lehrich, K., WąsiK, M., & KosMoL, J. (2018). Identifying the causes of deterioration in the surface finish of a workpiece machined on a rail wheel lathe. *Eksploatacja i Niezawodność*, *20*(3), 352-358.

[2] Steriade, M. (2003). *Neuronal substrates of sleep and epilepsy*. Cambridge University Press.

[3] Siddhpura, M., & Paurobally, R. (2012). A review of chatter vibration research in turning. *International Journal of Machine tools and manufacture*, *61*, 27-47.

[4] Quintana, G., & Ciurana, J. (2011). Chatter in machining processes: A review. *International Journal of Machine Tools and Manufacture*, *51*(5), 363-376.

[5] Pachori, R. B. (2023). *Time-frequency analysis techniques and their applications*. CRC Press.

[6] Wacker, M., & Witte, H. J. M. O. I. I. M. (2013). Time-frequency techniques in biomedical signal analysis. *Methods of information in medicine*, *52*(04), 279-296.

[7] Petrakov, Y., & Danylchenko, M. (2022). A time-frequency approach to ensuring stability of machining by turning. *Eastern-European Journal of Enterprise Technologies*, *6*(2), 120.

[8] Stavropoulos, P., Souflas, T., Papaioannou, C., Bikas, H., & Mourtzis, D. (2023). An adaptive, artificial intelligence-based chatter detection method for milling operations. *The International Journal of Advanced Manufacturing Technology*, *124*(7), 2037-2058.

[9] Basit, A., Khan, N. B., Ali, S., Muhammad, R., Abduvalieva, D., Khan, M. I., & Jameel, M. (2024). Chatter detection and suppression in machining processes: a comprehensive analysis. *International Journal on Interactive Design and Manufacturing (IJIDeM)*, *18*(6), 3751-3771.

[10] Kuljanic, E., Totis, G., & Sortino, M. (2009). Development of an intelligent multisensor chatter detection system in milling. *Mechanical Systems and Signal Processing*, *23*(5), 1704-1718.

[11] Basit, A., Khan, N. B., Ali, S., Muhammad, R., Abduvalieva, D., Khan, M. I., & Jameel, M. (2024). Chatter detection and suppression in machining processes: a comprehensive

analysis. *International Journal on Interactive Design and Manufacturing (IJIDeM)*, *18*(6), 3751-3771.

[12] Navarro-Devia, J. H., Chen, Y., Dao, D. V., & Li, H. (2023). Chatter detection in milling processes—a review on signal processing and condition classification. *The International Journal of Advanced Manufacturing Technology*, *125*(9), 3943-3980.

[13] Zhang, X., Wan, L., & Ran, X. (2024). Research progress on the chatter stability in machining systems. *The International Journal of Advanced Manufacturing Technology*, *131*(1), 29-62.

[14] Basit, A., Khan, N. B., Ali, S., Muhammad, R., Abduvalieva, D., Khan, M. I., & Jameel, M. (2024). Chatter detection and suppression in machining processes: a comprehensive analysis. *International Journal on Interactive Design and Manufacturing (IJIDeM)*, *18*(6), 3751-3771.

[15] Zhang, X., Wan, L., & Ran, X. (2024). Research progress on the chatter stability in machining systems. *The International Journal of Advanced Manufacturing Technology*, *131*(1), 29-62.

[16] Faassen, R. P. H. (2007). Chatter prediction and control for high-speed milling: modelling and experiments.

[17] Mohammadi, Y. (2022). *Chatter vibrations in robotic milling considering structural nonlinearity* (Doctoral dissertation).

[18] Gao, D., Liao, Z., Lv, Z., & Lu, Y. (2015). Multi-scale statistical signal processing of cutting force in cutting tool condition monitoring. *The International Journal of Advanced Manufacturing Technology*, *80*(9), 1843-1853.

[19] Marinkovic, D., Antic, A., Knezev, M., Mladjenovic, C., & Zivkovic, A. (2024). THE INFLUENCE OF THE CUTTING PARAMETERS ON THE SURFACE ROUGHNESS AND VIBRATION SIGNAL IN THE TURNING PROCESS. *MM Science Journal*.

[20] Arslan, H., ER, A., Orhan, S., & Aslan, E. (2016). Tool condition monitoring in turning using statistical parameters of vibration signal. *International Journal of Acoustics and Vibrations*, *21*(4).

[21] Sarna, M. L. A., Hossain, M. R., & Islam, M. A. (2024). Comparative analysis of stft and wavelet transform in time-frequency analysis of non-stationary signals. *International Journal of Novel Research in Engineering and Science*, *11*(1), 72-78.

[22] Wacker, M., & Witte, H. J. M. O. I. I. M. (2013). Time-frequency techniques in biomedical signal analysis. *Methods of information in medicine*, *52*(04), 279-296.

[23] Chen, B., Zhao, S. L., & Li, P. Y. (2014). Application of Hilbert-Huang Transform in Structural Health Monitoring: A State-of-the-Art Review. *Mathematical Problems in Engineering*, *2014*(1), 317954.

[24] Fu, K., Qu, J., Chai, Y., & Dong, Y. (2014). Classification of seizure based on the time-frequency image of EEG signals using HHT and SVM. *Biomedical Signal Processing and Control*, *13*, 15-22.

[25] Hase, A., Wada, M., Koga, T., & Mishina, H. (2014). The relationship between acoustic emission signals and cutting phenomena in turning process. *The International Journal of Advanced Manufacturing Technology*, *70*(5), 947-955.

[26] Asadi, R., Niknam, S. A., Anahid, M. J., & Ituarte, I. F. (2023). The use of wavelet transform to evaluate the sensitivity of acoustic emission signals attributes to variation of cutting parameters in milling aluminum alloys. *The International Journal of Advanced Manufacturing Technology*, *126*(7), 3039-3052.

[27] Ravindra, H. V., Srinivasa, Y. G., & Krishnamurthy, R. (1997). Acoustic emission for tool condition monitoring in metal cutting. *Wear*, *212*(1), 78-84.

[28] Basit, A., Khan, N. B., Ali, S., Muhammad, R., Abduvalieva, D., Khan, M. I., & Jameel, M. (2024). Chatter detection and suppression in machining processes: a comprehensive analysis. *International Journal on Interactive Design and Manufacturing (IJIDeM)*, *18*(6), 3751-3771.

[29] Sener, B., Gudelek, M. U., Ozbayoglu, A. M., & Unver, H. O. (2021). A novel chatter detection method for milling using deep convolution neural networks. *Measurement*, *182*, 109689.

[30] Tran, M. Q., Liu, M. K., & Elsisi, M. (2022). Effective multi-sensor data fusion for chatter detection in milling process. *ISA transactions*, *125*, 514-527.

[31] Özger, M., Başakın, E. E., Ekmekcioğlu, Ö., & Hacısüleyman, V. (2020). Comparison of wavelet and empirical mode decomposition hybrid models in drought prediction. *Computers and Electronics in Agriculture*, *179*, 105851.

[32] Shrivastava, Y., Singh, B., & Sharma, A. (2018). Identification of chatter in turning operation using WD and EMD. *Materials today: proceedings*, *5*(11), 23917-23926.

[33] Pankaj, G., Bhagat, S., & Yogesh, S. (2022). Robust Techniques for Signal Processing: A Comparative Study. *Evergreen*, *9*(2), 404-411.

[34] Lampropoulos, G., Siakas, K., & Anastasiadis, T. (2019). Internet of things in the context of industry 4.0: An overview. *International Journal of Entrepreneurial Knowledge*, *7*(1).